

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 December 2003 (18.12.2003)


PCT

(10) International Publication Number  
WO 03/103910 A1

- (51) International Patent Classification<sup>7</sup>: B27G 5/02, B27B 27/08
- (21) International Application Number: PCT/EP03/05849
- (22) International Filing Date: 4 June 2003 (04.06.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0213194.4 8 June 2002 (08.06.2002) GB
- (71) Applicant (for all designated States except US): **BLACK & DECKER INC** [US/US]; Drummond Plaza, 1423 Kirkwood Highway, Newark, DE 19711 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **ROSSETTI, Mirco** [IT/IT]; Via Bottinelli, 4, I-06100 Perugia (IT). **BETTACCHINI, Marcello** [/]; \*\* (IT).
- (74) Agents: **BELL, Ian, Stephen** et al.; Black & Decker, 210 Bath Road, Slough SL1 3YD (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declarations under Rule 4.17:**  
— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,

[Continued on next page]

(54) Title: MITRE SAW WITH ADJUSTABLE FENCE



(57) Abstract: A mitre saw (110) having an operable cutting blade (122) pivotally supported relative to a work surface (114) and displaceable in a first cutting plane which intersects the work surface along a first cutting line (X-X), further comprising an adjustable elongate fence (134) angularly displaceable relative to the first cutting line X-X whereby the fence is adjustably mounted on and supported by the work surface (114).



WO 03/103910 A1



KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US
- of inventorship (Rule 4.17(iv)) for US only

**Published:**

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## MITRE SAW WITH ADJUSTABLE FENCE

The present invention is directed to mitre saws and more particularly to power driven mitre saws where the angle between the cutting blade and the support fence is adjustable to provide for a wide range of cutting angles.

5 Power driven mitre saws of this type are well known and commonly used on building sites and by those involved in woodworking to allow for ease of cutting various lengths of wood to have required simple or complex (compound) cut angles. The basic type of mitre saw simply comprises a circular saw blade which is operable in a cutting plane substantially perpendicular to a work surface on which the  
10 workpiece to be cut is supported by an appropriate fence. The plane in which the blade is operable can then be angularly adjusted relative to the fence (which is fixed relative to the base of the mitre saw) to change the cutting angle relative thereto. Alternatively, such mitre saws may additionally further provide for the blade to be adjustably inclined relative to the work surface to provide for bevel cuts (or  
15 compound mitre cuts) whereby the blade is not only inclined in a first plane relative to the work surface (and thus the workpiece) but also has a second angular component relative to the fence. Such compound mitre cuts are commonly used for producing roofing joints. One further design variant of mitre saws allow the blade not only to be raised and lowered relative to the work surface but also, in the use of cross cut mitre  
20 saws, to be displaced longitudinally outwardly of such a work surface to produce a sliding compound mitre saw. However, in all such variants, the basic operation of the mitre saw remains constant, that is: the circular saw blade employed is operative in a first cutting plane relative to the work surface where this plane intersects the work surface at a first cutting line and this cutting line can be angularly inclined relative to  
25 a fixed fence on the mitre saw to define the appropriate mitre angle required. Typical prior art mitre saws comprise a fixed base assembly having a rotatable table or work surface, on which the adjustable saw blade securely mounted for corresponding rotation relative to the base and is also pivotally mounted so that a user can downwardly pivot the saw assembly to bring the blade towards this table, as shown in  
30 Figure 1. The base assembly has fixedly mounted thereon the mitre fence, so that the

table not only rotates relative to the base assembly but also relative to the fence. In this manner, since the cutting plane defined by the adjustable blade intersects the rotatable table assembly in a first cutting line, the cutting line of such blade can then be angularly inclined relative to the fence to select the mitre angle. Once a mitre angle has been selected the table is then releasably secured to the base unit to lock the saw the appropriate angle. One example of a mitre saw of this type is disclosed in the Applicants corresponding European Patent Application EP 0 949 048 showing a portable mitre saw of this type, although the same principle of operation is equably applicable on prior art stationary mitre saws employing larger work surfaces or bases.

However, whilst this type of conventional mitre saw provides for an efficient manner of adjusting the mitre angle, the mechanisms employed to provide for such a rotatable table releasably secured to a base assembly are somewhat complex and expensive to manufacture and service.

It is therefore an object of the present invention to provide a mitre saw with an alternative mechanism for varying the mitre angle which is more simplistic and less expensive to manufacture than current methods of adjusting the mitre angle on such saws.

Therefore, according to the present invention there is provided a mitre saw having an operable cutting blade supported relative to a work surface and displaceable in a first cutting plane wherein this cutting plane intersects the work surface along a first cutting line, the mitre saw further comprising an adjustable elongate fence angularly displaceable relative to this first cutting line, characterised in that the fence is mounted on and supported by the work surface so as to be angularly displaceable thereon relative to said cutting line. In this manner, the work surface is fixed relative to a support frame, removing the necessity of providing a rotatable table, such that the fence is mounted on this work surface and is adjustable relative thereto to vary the angle between the fence and the cutting line, and thus the blade. Such mitre saws may further comprise means for inclining the cutting plane relative to the work surface, as is conventional in mitre saws used for producing bevel cuts, whereby this cutting

plane still intersects the work surface along said cutting line and whereby the mitre angle is again varied by displacing the fence angularly with respect to this cutting line.

5            Preferably, the work surface will comprise a recessed channel along the first cutting line for accommodating the blade when the blade is displaced in this first cutting plane so as to pass through the cutting line. Preferably, the fence will comprise at least one releasable restraint member for restraining the fence to the work surface in a plurality of angularly adjusted orientations relative to the cutting line so  
10    that the user may selectively adjust the mitre angle required and lock the fence in the appropriate position. In addition, the present invention also provides for a mitre saw which allows the fence to be longitudinally adjusted along the cutting line so as to vary the operative cutting depth provided by such mitre saws. This feature is particularly beneficial for use with compound sliding mitre saws for cutting objects  
15    having varied thicknesses and depth.

            Preferably, the fence itself will extend over the cutting line so as to support a workpiece either side of the cutting line during the cutting operation. Here, the fence will usually have a recess form therein for overlying the cutting line and, in particular,  
20    the recessed channel in the work surface, so as not to inhibit or engage the blade as it performs the cutting operation and passes through the work surface. As such, it is preferable that the fence will comprise at least two separate elongate sections, each presenting a support face extending perpendicular to the work surface in the same fence plane, with the recess here formed as a break between these two separate  
25    sections. At least one of the adjacent free ends of the separate sections of the fence are inclined longitudinally outwardly of this break so as to provide an inclined support surface to the object to be cut which accommodates the blade when the cutting plane is inclined relative to the work surface.

30           Where the fence comprises separated sections disposed either side of the cutting line, the separate sections are preferably interconnected by a rigid support element extending therebetween so as to be remote from the recess. Usually this rigid support

element will be substantially U-shaped extending out of the fence plane so as not to interfere with the blade in the cutting operation. Alternatively, this support element may extend substantially in the fence plane so as to be disposed below the work surface, again to avoid interference with the blade during the cutting operation.

5 Alternatively, the separate sections of the fence may not be interconnected but may both be restrained in the same fence plane independently of one another, maintaining a constant angle of inclination of the fence relative to the cutting line.

It is preferable that the fence is pivotally mounted on the work surface about at least one pivot axis, wherein such a pivot axis is usually disposed substantially adjacent to the cutting line.

10

Preferably, the work surface will comprise at least one guide track and the fence will comprise at least one track following member in co-operative sliding engagement therewith, which facilitates the angular adjustment of the fence about the cutting line.

15 In one embodiment, the track itself may be linear whereby it is therefore preferable that the or the at least one track following member is longitudinally adjustable along the elongate fence as the fence is pivoted about the pivot axis. Alternatively, or in combination, the work surface may in fact comprise at least two tracks and the fence

20 comprise at least two track following members for co-operating engagement therewith. Again one or both of the track following members may be longitudinally adjustable about this elongate fence and the fence may optionally utilise a fixed pivot axis or may be simply inclined between the two tracks themselves relative to the cutting line.

25

Alternatively, the or all of the tracks may be arcuate, preferably disposed to be coaxial with the pivot axis where used. In this situation, the track following members may be securely fixed to the fence so as to follow the arcuate paths coaxial with the pivot axis. Alternatively, the fence may be pivotally mounted about the or at least one

30 of the track following members and so to be both slideably adjustable relative to the cutting line in a longitudinal direction and also angularly displaceable thereabouts.

It is usual that the or at least one of the track follower means would form at least one of the releasable restraint members for restraining the fence to the work surface. Here it is usual that such releasable restraint members are rotatably adjustable to effect such engagement with the work surface, usually effecting screw threaded engagement with a washer or nut member disposed within the track so as to exert a compressive force on the work surface disposed between such washer and the fence.

In an alternative embodiment of the present invention, such mitre saws may employ work surfaces comprising an array of first engagement means for co-operative releasable engagement with at least one second engagement means on the fence for restraining the fence on the work surface at a pre-determined angular inclination relative to the cutting line, wherein engagement of the second engagement means with a different one of the array of first engagement means restrains the fence in a second pre-determined angle relative to the cutting line. Usually the first engagement means will comprise an array of holes in the work surface and the second engagement means will comprise at least one projection member for engagement with one of the array of holes to effect appropriate angular alignment relative to the cutting line. Such projection members may comprise elongate members for co-operating engagement in corresponding angularly inclined (relative to cutting line) elongate slots, or may further comprise a plurality of projections for engagement with a plurality of holes to define the angular orientation, wherein the holes are appropriately positioned on the work surface so that engagement therewith would facilitate an appropriate angular inclination relative to the cutting line. It is usual that the projection members may be longitudinally adjustable along the fence.

A preferred embodiment of the present invention will now be described, by way of example only, with reference to the accompanying illustrative drawings in which:

Figure 1 shows a mitre saw according to the prior art; and

Figure 2 shows a mitre saw according to the present invention; and

Figure 3 is a plan view from above of the mitre saw of Figure 2, illustrating an adjustable fence; and

Figure 3a is a cross sectional view of the fence of the mitre saw of Figure 3 along the lines III-III illustrating a fence restraint member; and

Figure 4 illustrates a second embodiment of an adjustable fence according to the present invention; and

Figure 5 is a schematic illustration showing relative angular inclination of the cutting plane relative to the work surface of the mitre saw of Figure 2.

Figure 1 shows a conventional mitre saw according to the prior art. This mitre saw (10) comprises a fixed base assembly (12) having rotatably mounted thereon a table or work surface (14). Securely fixed to the rotatable work surface (14) is a saw assembly (16) which basically comprises a handle (18) (usually comprising a trigger switch, not shown) together with a motor housing (20) housing an electric motor (either mains operated or battery operated) with a conventional bearing assembly and output for driving a circular saw blade (22), which is shown here housed behind an automatically adjustable blade guard (24). The entire saw assembly (16) is mounted on a conventional hinge arrangement (26) so as to pivot about an axis (A), so as to pivotally displace the saw blade (22) towards the work surface (14) in a first cutting plane (5). Again, as is conventional for mitre saws of this type (and, as such, will not be described in great detail herein), the adjustable blade guards (24) are automatically displaced about the circumference of the blade housing (25) as the saw assembly (16) is pivotally displaced towards the table (14), so as to expose the rotating circular saw blade (22) as it approaches this work surface and a workpiece mounted thereon.

The flat circular saw blade (22) defines a first cutting plane (5) through which pivotal displacement of the saw (16) moves the blade (22). The plane in which this flat blade itself lies, perpendicular to axis A, is defined as the cutting plane and is represented by the plane through which the blade itself is pivotally displaceable and shown illustratively in Figure 1 as plane (5). This cutting plane subsequently intersects the work surface or table (14) along a cutting line illustrated by the line X-X in Figure 1 and along which cutting line X-X the table is provided with a elongate groove or channel (30) which will accommodate the circular saw blade as it is



pivotally displaced into cutting engagement with a workpiece placed on this work surface.

The mitre saw (10) further comprises a fence assembly which comprises two  
5 separate sections (34a, 34b) each rigidly secured to the base member (12), and  
restrained from rotation thereto. This fence assembly (32) presents a workpiece  
supporting portion against which a workpiece (such as a length of timber) may be  
disposed and held firm during the cutting operation. This fence (32) further  
10 comprises a gap or recess (36) overlying the cutting line X-X so as not to inhibit or  
engage the rotating saw blade during the cutting operation. As illustrated in Figure 1,  
the adjacent end faces (38a and 38b) of the fence disposed either side of this recess  
(36) may be either vertical (38a) (where the saw blade (22) is to be maintained in a  
cutting plane which is not angularly adjustable relative to the work surface) or  
alternatively, if the mitre saw is a compound mitre saw, whereby the hinged  
15 connection of the saw assembly (16) is rotatable (so as to incline the axis (A) and thus  
the angle of inclination of the cutting plane relative to the work surface (as will be  
described below)) then the end face (38b) of the fence (34a) is inclined so as to  
facilitate operation of and accommodate the blade when in such an inclined cutting  
plane relative to the work surface (14).

20

The mitre saw (10) of Figure 1 illustrates a mitre saw orientated for cutting at  
right angles. Here the cutting line X-X is disposed substantially at an angle  $\alpha$  of  $90^\circ$   
relative to the fence (34) so as to provide a right angled cut through a workpiece  
placed on this saw adjacent to the fence as the saw blade (22) is pivotally lowered into  
25 engagement therewith.

25

In order to vary the mitre angle of cut of such saw, the rotatable table or work  
surface (12) is rotated relative to the fixed base assembly by releasing a fixing  
mechanism (40) between the rotatable table (14) and the base station (12). In the  
30 prior art example of Figure 1, a rotatable screw threaded engagement member (40)  
provides a releasable locking mechanism between two work surfaces and the base.  
As is conventional in the art, rotation of this work surface (14) in the direction shown

30

generally by arrows B in Figure 1 effects angular displacement of cutting line X-X relative to the fixed base (12) and hence fixed fence (34), thereby varying the angle  $\alpha$  therebetween and hence the mitre cutting angle. The work surface is provided with an indicia marking (44) which is read against a fixed angular scale (or indicia) (46) on the base (12) to determine the exact angle  $\alpha$  between the cutting line X-X and the fence (34). In this manner, the operator can pre-select the required mitre angle by adjustment of the rotatable work surface until the correct angular alignment is achieved, and the rotatable work surface then secured in engagement with the base station (12) at this pre-determined angle.

10

Whereas the prior art mitre saw (10) shown in Figure 1 is a portable mitre saw, in that it has a reduced size working surface (14) and base assembly (12), (which base assembly may receive detachable legs), Figure 2 shows a table mitre saw (110) (which again is portable or may be used as a stationary unit) which adopts the similar principle of mitre saw operation to that used in portable mitre saws (10) of the type shown in Figure 1. In this respect, it is to be appreciated that the invention is equally applicable to both portable mitre saws and table mitre saws.

15

Referring now to Figure 2, showing the present invention, the table mitre saw (110) again comprises a saw assembly (116) having a handle (118) with a trigger switch (119) attached to a motor housing (112) which is connected through a bearing assembly (not shown) to a circular saw blade (122) mounted within a blade housing (125) and surrounded by a displaceable blade guard (124). This saw assembly (116) is mounted on a table or working surface (114) which is securely mounted on four sturdy legs (117) to provide a stationary mitre saw (however whilst the work surface (114) here is mounted on legs (117), the current invention is equally applicable to a portable mitre saw of the type shown in Figure 1 whereby in such a situation the work surface (14) of Figure 1 would be integral and fixed with respect to the base station (12)). Again, the saw assembly (116) is pivotally mounted about an axis (A) through a conventional hinge arrangement so as to allow pivotal displacement of the saw

20

25

30

blade towards the work surface (114) about this axis (A), as described with reference to Figure 1.

The work surface (114) has an elongate recess or groove (130) for  
5 accommodating the circular saw blade as it passes through the upper surface of this work surface (114). The saw (116) in this example is operated and controlled via a power box (135) receiving power input from a mains source. As in the prior art embodiment of Figure 1, the circular saw blade (122) is also operative and rotatable in  
10 a first cutting plane which intersects with the work surface (114) along a cutting line shown again as X-X in Figure 2. The saw (110) further comprises an adjustable fence member (134), which fence member is pivotally adjustable over the surface of the work surface (114) so as to vary the angle between this fence (134) and the cutting line X-X as will be more readily understood with reference to Figure 3.

15 Figure 3 shows a schematic plan view from above of the mitre saw (110) of Figure 2 having the saw assembly (116) removed. The engagement between the saw assembly (116) and the work surface (114) is shown schematically at (150), showing the pivot axis (A) disposed at right angles to the cutting line X-X.

20 As can be seen from Figures 2 and 3 the saw assembly (116) and work surface (114) are secured relative to one another and are fixed relative to the base (in this situation legs (117)) so as to be non rotatably mounted thereon. Instead, the fence (134) is mounted on the work surface (114) to be angularly adjustable relative thereto, and adjustable relative to the cutting line X-X.

25 Since the pivot axis A (about which the circular saw blade is able to pivot) is now fixed relative to the work surface (114) then the cutting plane (as previously described), is also fixed relative to the work surface (114) and is considered to be represented by a plane extending out of the paper, so as to be perpendicular thereto,  
30 along the line X-X of Figure 3.

Here the fence (134) is substantially L-shaped in cross section (Figure 3a and Figure 2) comprising an upright workpiece engaging face (152), lying in a fence plane extending substantially perpendicular to the work surface, and has a rear stabilising flange (153) which lies against the work surface (114). Again, the fence (134) is divided into two separate sections (134a and 134b) forming a channel or recess (136) therebetween, similar to the recess formed in the fence (34) of Figure 1. As will be appreciated from the Figures, this recess (136) overlies the recessed channel (130) of the work surface (114) (and hence the cutting line X-X) and so allows for the saw blade to pass between the fence without engagement therewith.

In this embodiment of the current invention, the two distinct sections (134a,134b) of the fence are interconnected by a substantially U-shaped rigid support element (157) (Figure 3), which U-shaped support (157) is disposed rearwardly of the engaging face (152) and remote from the aperture (136) so as not to interfere with the saw blade during operation of the mitre saw. Alternatively, this U-shaped support section could be formed so as to pass through the table and underlie both the table (114) and the channel (130) again so as to not interfere with the saw blade in operation. In such an alternative embodiment, the faces (152) of the fence (134) define a substantially perpendicular plane to the work table (114) (fence plane) whereby the support member (157) would then lie substantially in this fence plane. The main function of the support member (157) is to restrain the two separate sections (134a and 134b) from relative angular or longitudinal displacement to one another so that their faces (152) are maintained substantially co-planar in this fence plane.

The fence (134) (and fence plane) is angularly displaceable relative to the cutting line X-X (angle  $\beta$ ). This angular adjustment is achievable by a variety of methods and techniques all of which are considered to fall within the scope of the current invention. The preferred embodiment shown in Figure 3 requires the fence (134) to be pivotally attached via a pivot member (163) having a pivot axis extending perpendicular to the work surface (114), which is disposed on the inner end of fence member (134b), with the fence being rotatably displaceable about such pivot member. The pivot member comprises a pin member extending through the fence (134) into a

corresponding aperture within the table (114). The second fence section (134a) is further provided with a restraint member (165) which passes through this fence section for co-operative engagement with the work surface (114) to releasably engage therewith to secure the adjustable fence (134) in its desired angular orientation. This

5 restraint member (165) (shown more clearly in Figure 3a) comprises a rotatable knurled knob (167) having an elongate screw threaded section (169) for co-operative screw threaded engagement with a nut member (171) slideably received within a longitudinally extending undercut slot (173) formed within the work surface (114). The nut member (171) is slideably displaceable within this undercut slot (173) but

10 restrained from rotational displacement therein (ie. such as by use of a hexagonal or square nut which engages the side walls of such slot). Such an arrangement is conventional and it will be appreciated that when the restraint member is rotated clockwise so as to effect screw threaded arrangement between the projection (169) and the nut (171), the nut (171) is forced upwardly along the length of the projection

15 (169), thereby engagement with the shoulders (175) of the undercut slot (173), resulting in a compressive force being applied between the nut and the knob (167) thereby compressing the fence (134) into engagement with the table to frictionally restrain the fence in engagement therewith. When the knob is rotated in an anti clockwise direction such compressive force is relieved allowing the restraint member

20 (165) to be slideably displaceable along the channel (173) as the fence (134) is pivoted about pivot point (163) to change the angular displacement  $\beta$  between the fence (134) and the cutting line X-X. The fence section (138) further comprises an elongate aperture (180) for accommodating the restraint member (165) to allow the restraint member (165) to be longitudinally displaceable along the fence member

25 (134a) to compensate for the longitudinal displacement of the fence member (134a) relative to the channel (173) during the pivotal displacement about pivot point (163). Figure 3 also illustrates that the work surface (114) may be further provided with indicia markings (181) defining appropriate angular configurations  $\beta$  to allow the user to correctly set angle  $\beta$  as required by aligning the fence (34) with such markings.

The current invention further provides for longitudinal adjustment of the fence (134) longitudinally along the cutting line X-X. Since the fence (134) is simply pivotally engaged with the work surface (114) by use of a pin member through the pivot point (163) then, by longitudinal adjustment of this pivot axis, in a direction  
5 parallel to the cutting line X-X and subsequent engagement with an alternatively longitudinally displaced hole (183) then the entire fence (134) can be displaced along the line X-X and again pivotally operated in the manner previously described. This longitudinal adjustment of the fence provides an additional advantage of allowing different sized workpieces to be cut. Additionally, the indicia (181) may be reset so  
10 as to be correctly aligned with the alternative pivot axis position (183) to again ensure the user is able to correctly determine angle  $\beta$  by use of such indicia being aligned with the fence plane. The longitudinal adjustment of the fence may be particularly beneficial when used in conjunction with a sliding compound mitre saw.

It will also be appreciated that whilst the pivot point (163) is shown substantially adjacent to the cutting line X-X, this pivot axis could be alternatively displaced anywhere along the length of the fence section (134b) provided that the aperture (136) is sufficiently large to prevent either of the fence sections (134a and 134b) overlying the cutting line X-X in any one of the desired angular settings  $\beta$ .

Figure 4 shows an alternative arrangement of an adjustable fence mechanism for use with the mitre saw (110) of Figure 2 whereby the pivot axis (163) of the embodiment shown in Figure 3 is removed and both sections (134a and 134b) of the fence (134) are provided with restraint means (165) with corresponding,  
25 longitudinally extending apertures (180) (as previously described with reference to Figure 3)). Both restraint members (165) co-operate with corresponding longitudinally extending slots (173) formed in the work surface (114) in the manner previously described with reference to Figure 3. In this situation, the fence is slideably adjustable along both slots (173) by releasing the restraint members (165),  
30 allowing the fence plane to be aligned between two sets of indicia (181) designating the appropriate mitre angle (one each associated with each slot (173)), with the

operator ensuring that the recess (136) overlies the cutting line X-X. Again for this embodiment, the fence (134) is longitudinally displaceable along the cutting line X-X by appropriate displacement along the channels (173), whereby the indicia associated with each channel (173) may also be displaceable and reset in this longitudinal direction to allow correct determination of the angle  $\beta$ . Once the appropriate angle  $\beta$  has been determined by alignment of the fence (134) with the appropriate indicia, both of the restraint members (165) may then be engaged to restrain the fence (134) in that desired position.

The current invention is also applicable to compound mitre saws whereby the cutting plane in which the circular saw blade is operable, is angularly adjustable relative to the work surface (114). This is clearly shown in Figure 5 showing a schematic cross section through the mitre saw (110) of Figure 2, schematically illustrating the cutting plane (300) when the blade (122) is in the position shown in Figure 2 and disposed substantially at right angles to the work surface (114), wherein the blade is vertically displaceable into and out of engagement with a workpiece mounted on the table (114) (shown generally by arrow (302)). However, if the blade (122) is angularly adjusted to a second cutting plane (304) (as is conventional in compound mitre saws) it will again be appreciated that this cutting plane (304) will intersect the work table (114) along the same cutting line X-X, although the cutting plane will be angularly disposed relative to the work surface (114). However, since the fence (134) is angularly adjustable on the work surface (114) relative to the cutting line X-X then its effectiveness will not be affected by angular inclination of the cutting plane (304). Figure 5 also illustrates the benefit of providing the cutting fence with inclined edges (386) adjacent to the recess (136) to accommodate such an inclined cutting plane so that the fence (134) will not interfere or engage the blade (122) as it is displaced towards the work surface (114) along this inclined cutting plane (304).

It will be appreciated that there are many variations to the specific embodiments described herein which still fall within the general scope of the current invention, where the fence of such a mitre saw is angularly adjustable relative to a fixed work

surface (114). In particular, the slots (173) shown in Figures 3 and 4 need not be parallel to the cutting line X-X and may in fact be arcuate (and, in Figure 3, co-axial with the pivot point (163)) with the associated restraint member (165) thereby secured from longitudinal displacement on the fence (134) and simply able to follow the pre-defined arcuate path when undergoing angular displacement.

In addition, whilst the preferred embodiment has described the restraint members (165) being slideably adjustable along slots (173) an alternative embodiment to that shown in Figure 3 may employ an engagement mechanism mounted on the fence (134) which is only co-operable with the table at pre-determined angular positions (for example every  $5^\circ$ ). An example of this embodiment employs the use of a spring biased projection member, biased towards engagement with the work surface (114), for co-operable engagement with an array of apertures formed therein at pre-determined angular orientations. Thus to effect a change of angle  $\beta$  a spring biased member is lifted out of engagement with one such hole or aperture in the work surface (114), whereby subsequent angular adjustment of the fence (134) about the axis (163) displaces such spring biased projection until it overlay a further hole in the work surface, and released into engagement therewith. Again such holes in the work surface could be arrayed along an arcuate path coaxial with the axis (163) or alternatively the spring bias projection could be slideably mounted on the fence (134) with the array of holes being substantially linear and parallel to the cutting line X-X. Each hole would be representative of a pre-determined angular adjustment of  $\beta$ .

Also, whilst it is preferable to rigidly interconnect to the two sections (134a and 134b) of the fence (134) by use of the support element (157), this is not essential to the operation of the invention. It is envisaged that both of the sections (134a and 134b) could be independently adjustable on the work surface (114). One example of such a configuration would be for each section (134a, 134b) to have, as a restraint member, an elongate downwardly extending projection for complimentary co-operation with elongate slots formed within the work surface at pre-determined orientations to the cutting line which will automatically align the two fence sections



(134a, 134b) at pre-determined angular orientations relative to the cutting line X-X. Alternatively, it is possible that both separate sections (134a and 134b) could each employ two restraint members (165) both located in the same slots (180) and each engageable with two parallel channels (173) to provide for angular adjustment of the fence plane by alignment with pre-determine indicias marked on the work surface (114).

Still further, where the two sections (134a and 134b) of the fence (134) are not interconnected and are thus independently adjustable on the work surface (114) it would also be possible for each of these two sections to be disposed at completely different angles relative to the cutting line X-X. Here, for example, each section may be disposed at 45° to the cutting line X-X so as to form a substantial right angle between the two fence members which would allow the accurate positioning of a right angled workpiece relative to the cutting line X-X.

15

Whilst the preferred embodiment herein described relates to mitre saws having circular saw blades, the current invention is equally applicable to mitre saws having power driven linear reciprocating blades which are displaceable towards the work surface in the previously described cutting plane.

20

Finally, the restraint means (165) described in the examples shown herein are by way of reference only and it is well understood and known within the art to provide many alternative forms of releasable engagement means for restraining adjustable articles to a work surface, all of which are considered to be incorporated within the current invention.

25

**CLAIMS**

1. A mitre saw having an operable cutting blade supported relative to a work surface and displaceable in a first cutting plane wherein said cutting plane intersects said work surface along a first cutting line, said mitre saw further comprising an adjustable elongate fence angularly displaceable relative to said first cutting line;  
5 characterised in that said fence is mounted on and supported by said work surface so as to angularly displaceable thereon relative to said cutting line.

2. A mitre saw as claimed in claim 1 wherein said cutting blade is adjustable so as to adjustably incline the cutting plane relative to the work surface.

10

3. A mitre saw as claimed in either of the preceding claims wherein said work surface is non-adjustably mounted on a support frame.

15

4. A mitre saw as claimed in any one of the preceding claims wherein said work surface comprises a recessed channel along said first cutting line for accommodating said blade when displaced in said first cutting plane.

20

5. A mitre saw as claimed in any one of the preceding claims wherein said fence comprises at least one releasable restraint member for restraining said fence to said work surface in a plurality of angularly adjusted orientations relative to said cutting line.

25

6. A mitre saw as claimed in any one of the preceding claims wherein said fence is longitudinally adjustable along said cutting line.

7. A mitre saw as claimed in any one of the preceding claims wherein said fence extends over said cutting line.

30

8. A mitre saw as claimed in claim 7 wherein said fence comprises a recess for overlying said cutting line in said work surface.

9. A mitre saw as claimed in claim 8 wherein said fence comprises at least two separate elongate sections each presenting a support face extending perpendicular to said work surface in the same fence plane, with said recess formed by a break between said separate sections.

5

10. A mitre saw as claimed in claim 9 wherein at least one of the adjacent free ends of said separate sections is inclined longitudinally outwardly of said break so as to accommodate said blade when said cutting plane is inclined relative to said work surface.

10

11. A mitre saw as claimed in either claim 9 or claim 10 wherein said separate sections disposed either side of said cutting line are interconnected by a rigid support element extending between said sections remote from said recess.

15

12. A mitre saw as claimed in claim 11 wherein said support element extends outside of said fence plane.

13. A mitre saw as claimed in any one of the preceding claims wherein said fence is pivotally mounted on said work surface about at least one pivot axis.

20

14. A mitre saw as claimed in any one of the preceding claims wherein said work surface comprises at least one guide track and said fence comprises at least one track follower member in cooperative sliding engagement therewith.

25

15. A mitre saw as claimed in claim 14 wherein said work surface comprises at least two tracks and said fence comprises at least two track follower members for respective cooperating engagement therewith.

30

16. A mitre saw as claimed in claim 14 or claim 15 wherein the or at least one track follower member is longitudinally adjustable along said elongate fence.

17. A mitre saw as claimed in any one of claims 14 to 16 wherein the or at least one track is linear.

18. A mitre saw as claimed in any one of claims 14 to 16 in which the or at least  
5 one track is arcuate.

19. A mitre saw as claimed in any one of claims 14 to 18 when appended to claim 13 wherein the fence is pivotally mounted about the or at least one of said track follower members

10

20. A mitre saw as claimed in claim 13 or any one of claims 14 to 18 when appended to claim 13 wherein said pivot axis is fixed between said fence and said work surface.

15 21. A mitre saw as claimed in any one of claims 14 to 19 when appended to claim 5 wherein the or at least one of said track follower means forms said at least one releasable restraint member.

22. A mitre saw as claimed in claim 21 wherein said releasable restraint member is  
20 rotatably adjustable to effect engagement with said work surface.

23. A mitre saw as claimed in any one of claims 1 to 11 wherein said work surface comprises an array of first engagement means for cooperative releasable engagement with at least one second engagement means on said fence for restraining said fence on  
25 said work surface at a predetermined angular inclination relative to said cutting line, wherein engagement of said second engagement means with a different one of said array of first engagement means restrains said fence in a second predetermined angle relative to said cutting line.

30 24. A mitre saw as claimed in claim 23 wherein said first engagement means comprises an array of holes in said work surface and said second engagement means

comprises at least one projection member for engagement with one of said array of holes.

25. A mitre saw as claimed in claim 24 wherein said projection member is  
5 longitudinally adjustable along said fence.

26. A mitre saw substantially as herein described with reference to the accompanying drawings.

1/4




FIG. 1

2/4






FIG. 2







# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/EP 03/05849

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 B27G5/02 B27B27/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B27G B27B B23D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2001/001375 A1 (EVANS D SCOTT ET AL) 24 May 2001 (2001-05-24)  paragraph '0033! - paragraph '0039!; figures 1,4A,4B ---	1-5, 7-15,18, 20-24,26
X	US 4 995 288 A (DELLAPOLLA MICHAEL) 26 February 1991 (1991-02-26)  the whole document Y	1-6, 13-17, 19-22,26
X	US 4 245 533 A (BATSON WILLIAM A) 20 January 1981 (1981-01-20)  the whole document ---	25
	---	1,3-5, 7-9, 11-15, 18, 20-22,26
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

12 August 2003

Date of mailing of the international search report

20/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Huggins, J

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/05849

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 731 572 A (CROOKS R) 8 May 1973 (1973-05-08)  the whole document ----	1, 3, 5, 13, 14, 18, 20-22
X	US 3 498 345 A (SEXTON HENRY D) 3 March 1970 (1970-03-03)  the whole document ----	1, 3, 13-15, 17, 19
X	US 5 483 858 A (CHEN TONY) 16 January 1996 (1996-01-16) the whole document ----	1, 6, 13
X	US 3 918 340 A (WYNN GORDON WILLIAMS) 11 November 1975 (1975-11-11) the whole document ----	1, 23, 24
Y	----	25
A	SANTAPAU J M: "DOUBLE MITER-GAUGE JIG FOR CUTTING ANGLES" FINE WOODWORKING, TAUNTON PRESS, NEWTON, CT, US, no. 129, 1 March 1998 (1998-03-01), page 32 XP000738237 ISSN: 0361-3453 page 32; figure ----	1, 3, 5-7, 14-17
A	WO 99 02317 A (FREY HERMANN ; REINES WOLFGANG (DE); REICH MASCHF GMBH KARL (DE)) 21 January 1999 (1999-01-21) ----	
A	DE 33 08 749 A (OTT WERKZEUG & MASCHF G) 13 September 1984 (1984-09-13) -----	

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/05849

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001001375 A1	24-05-2001	US 2003140759 A1 CN 1238252 A EP 0941797 A2	31-07-2003 15-12-1999 15-09-1999
US 4995288 A	26-02-1991	NONE	
US 4245533 A	20-01-1981	CA 1130173 A1	24-08-1982
US 3731572 A	08-05-1973	NONE	
US 3498345 A	03-03-1970	NONE	
US 5483858 A	16-01-1996	NONE	
US 3918340 A	11-11-1975	AU 479394 A GB 1396872 A AU 4895672 A BE 783949 A1 CA 983822 A1 DE 2225136 A1 FR 2138994 A1 NL 7207075 A	16-05-1974 11-06-1975 16-05-1974 18-09-1972 17-02-1976 07-12-1972 05-01-1973 28-11-1972
WO 9902317 A	21-01-1999	DE 19729552 A1 AT 203195 T DE 59801049 D1 WO 9902317 A1 EP 0994766 A1	14-01-1999 15-08-2001 23-08-2001 21-01-1999 26-04-2000
DE 3308749 A	13-09-1984	DE 3308749 A1	13-09-1984

## PCT

REC'D 02 JUN 2004

WIPO

PCT

## INTERNATIONAL PRELIMINARY EXAMINATION REPORT

10/517099

(PCT Article 36 and Rule 70)

(Rationalised Report according to the Notice of the President of the EPO published in the OJ11/2001)

Applicant's or agent's file reference <b>P-WO-PR1080</b>	<b>FOR FURTHER ACTION</b> See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. <b>PCT/EP03/05849</b>	International filing date (day/month/year) <b>04/06/2003</b>	Priority date (day/month/year) <b>08/06/2002</b>
International Patent Classification (IPC) or national classification and IPC <b>B27G5/02</b>		
Applicant <b>BLACK &amp; DECKER INC</b>		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.


2. This **REPORT** consists of a total of 2 sheets, including this cover sheet.


☐ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consists of a total of \_\_\_\_\_ sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☐ Certain defects in the international application
- VIII ☐ Certain observations on the international application

Date of submission of the demand <b>08/01/2004</b>	Date of completion of this report <b>26/05/2004</b>
Name and mailing address of the IPEA/  European Patent Office, P.B. 5818 Patentlaan 2 NL-2280 HV Rijswijk - Netherlands Tel.: (+31-70) 340-2040 Fax: (+31-70) 340-3016	Authorized officer <b>SPIEGEL R</b> Tel. (+49-89) 2399 2828



**I. Basis of the report**

The basis of this international preliminary examination is the application as originally filed.

**V. Reasoned statement under Rule 66.2(a)(ii) with regard to novelty, inventive step or industrial applicability**

In light of the documents cited in the international search report, it is considered that the invention as defined in at least some of the claims does not appear to meet the criteria mentioned in Article 33(1) PCT, i.e. does not appear to be novel and/or to involve an inventive step (see international search report, in particular the documents cited X and/or Y and corresponding claim references).

**Box No. VIII (iv) DECLARATION: INVENTORSHIP** (only for the purposes of the designation of the United States of America)  
*The declaration must conform to the following standardized wording provided for in Section 214; see Notes to Boxes Nos. VIII, VII (i) to (iv) (in general) and the specific Notes to Box No. VIII (iv). (If this Box is not used, this sheet should not be included in the request.)*

**Declaration of inventorship (Rules 4.17(iv) and 51b(1)(a)(iv))**  
**for the purposes of the designation of the United States of America:**

I hereby declare that I believe I am the original, first and sole (if only one inventor is listed below) or joint (if more than one inventor is listed below) inventor of the subject matter which is claimed and for which a patent is sought.

This declaration is directed to the international application of which is forms a part (if filing declaration with application).

This declaration is directed to international application No. PCT/..... (If furnishing declaration pursuant to Rule 26ter).

I hereby declare that my residence, mailing address, and citizenship are as stated next to my name.

I hereby state that I have reviewed and understand the contents of the above-identified international application, including the claims of said application. I have identified in the request of said application, in compliance with PCT Rule 4.10, any claim to foreign priority, and I have identified below, under the heading "Prior Applications," by application number, country or Member of the World Trade Organization, day, month and year of filing, any application for a patent or inventor's certificate filed in a country other than the United States of America, including any PCT international application designating at least one country other than the United States of America, having a filing date before that of the application on which foreign priority is claimed.

Prior Applications: GB 0213194.4 .....

I hereby acknowledge the duty to disclose information that is known by me to be material to patentability as defined by 37 C.F.R. § 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the PCT international filing date of the continuation-in-part application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name: MIRCO ROSSETTI .....


Residence: ITALY .....

(city and either US state, if applicable, or country)

Mailing Address: VIA SPERANDIO 5 .....

PERUGIA, 06126, ITALY .....

Citizenship: ITALIAN .....

Inventor's Signature:  .....

(if not contained in the request, or if declaration is corrected or added under Rule 26ter after the filing of the international application. The signature must be that of the inventor, not that of the agent)

Date: 2/09/03 .....

(of signature which is not contained in the request, or of the declaration that is corrected or added under Rule 26ter after the filing of the international application)

Name: .....

Residence: .....

(city and either US state, if applicable, or country)

Mailing Address: .....

Citizenship: .....

Inventor's Signature: .....

(if not contained in the request, or if declaration is corrected or added under Rule 26ter after the filing of the international application. The signature must be that of the inventor, not that of the agent)

Date: .....

(of signature which is not contained in the request, or of the declaration that is corrected or added under Rule 26ter after the filing of the international application)

☐ This declaration is continued on the following sheet, "Continuation of Box No. VIII (iv)".

**Box No. VIII (iv) DECLARATION: INVENTORSHIP** (only for the purposes of the designation of the United States of America)  
*The declaration must conform to the following standardized wording provided for in Section 214, see Notes to Boxes Nos. VIII, VII (i) to (v) (in general) and the specific Notes to Box No. VIII (iv). If this Box is not used, this sheet should not be included in the request.*

**Declaration of inventorship (Rules 4.17(iv) and 518/1(a)(iv))  
 for the purposes of the designation of the United States of America:**

I hereby declare that I believe I am the original, first and sole (if only one inventor is listed below) or joint (if more than one inventor is listed below) inventor of the subject matter which is claimed and for which a patent is sought.

This declaration is directed to the international application of which it forms a part (if filing declaration with application).

This declaration is directed to international application No. PCT/..... (if furnishing declaration pursuant to Rule 26ter).

I hereby declare that my residence, mailing address, and citizenship are as stated next to my name.

I hereby state that I have reviewed and understand the contents of the above-identified international application, including the claims of said application. I have identified in the request of said application, in compliance with PCT Rule 4.10, any claim to foreign priority, and I have identified below, under the heading "Prior Applications," by application number, country or Member of the World Trade Organization, day, month and year of filing, any application for a patent or inventor's certificate filed in a country other than the United States of America, including any PCT international application designating at least one country other than the United States of America, having a filing date before that of the application on which foreign priority is claimed.

Prior Applications: GB.0213194.4 .....

I hereby acknowledge the duty to disclose information that is known by me to be material to patentability as defined by 37 C.F.R. § 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the PCT international filing date of the continuation-in-part application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name: MARCELLO BETTACCHINI .....

Residence: ITALY .....

(city and either US state, if applicable, or country)

Mailing Address: VIA GRANSCI, 75 .....

ELLERA DI CORCIANO, PERUGIA, 06074 ITALY .....

Citizenship: ITALIAN .....

Inventor's Signature: *Marcello Bettacchini* .....

(if not contained in the request, or if declaration is corrected or added under Rule 26ter after the filing of the international application. The signature must be that of the inventor, not that of the agent)

Date: 02/03/2003 .....

(of signature which is not contained in the request, or of the declaration that is corrected or added under Rule 26ter after the filing of the international application)

Name: .....

Residence: .....

(city and either US state, if applicable, or country)

Mailing Address: .....

Citizenship: .....

Inventor's Signature: .....

(if not contained in the request, or if declaration is corrected or added under Rule 26ter after the filing of the international application. The signature must be that of the inventor, not that of the agent)

Date: .....

(of signature which is not contained in the request, or of the declaration that is corrected or added under Rule 26ter after the filing of the international application)

☐ This declaration is continued on the following sheet, "Continuation of Box No. VIII (iv)".



**Box No. VIII (iii) DECLARATION: ENTITLEMENT TO CLAIM PRIORITY**

*The declaration must conform to the standardized wording provided for in Section 213; see Notes to Boxes Nos. VIII, VIII (i) to (v) (in general) and the specific Notes to Box No. VIII (iii). If this Box is not used, this sheet should not be included in the request.*

Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application specified below, where the applicant is not the applicant who filed the earlier application or where the applicant's name has changed since the filing of the earlier application (Rules 4.17(iii) and 51bis.1(a)(iii)):

in relation to this International Application MIRCO ROSSETTI and MARCELLO BETTACCHINI are entitled to claim priority of the earlier application number GB 0213194.4 by virtue of the following:-

the applicants are the inventors of this subject matter for which protection is sought by way of the earlier application. This declaration is made for the purposes of the United States of America only.

☐ This declaration is continued on the following sheet, "Continuation of Box No. VIII (iii)".